



FOR JAPANESE VEHICLES (JIS CMF series)

JIS GROUP	JIS No.		Capacity (A/H)		CCA -18°C	RC (MIN)	MAX. Overall Dimension(mm)				Lay-Out	Terminal	Weight (KGS)
	New	Old	20Hr	5Hr			L	W	H	TH			
B19	42B19R	NS40Z	40	28	332	52	187	127	199	219	1	B	9.60
	42B19L	NS40ZL	40	28	332	52	187	127	199	219	0	B	9.60
B24	55B24R	NS60	45	36	433	80	236	128	200	220	1	B	12.90
	55B24L	NS60L	45	36	433	80	236	128	200	220	0	B	12.90
	55B24RS	NS60S	45	36	433	80	236	128	200	220	1	A	12.90
	55B24LS	NS60LS	45	36	433	80	236	128	200	220	0	A	12.90
D23	65D23R	-	60	44	450	85	230	168	200	220	1	A	15.50
	65D23L	-	60	44	450	85	230	168	200	220	0	A	15.50
	75D23R	-	65	52	550	110	230	168	200	220	1	A	16.00
	75D23L	-	65	52	550	110	230	168	200	220	0	A	16.00
D26	48D26R	N50	50	40	350	81	260	168	200	220	1	A	15.20
	48D26L	N50L	50	40	350	81	260	168	200	220	0	A	15.20
	55D26R	N50Z	60	48	500	100	260	168	200	220	1	A	16.60
	55D26L	N50ZL	60	48	500	100	260	168	200	220	0	A	16.60
	85D26R	NS70	70	56	630	133	260	168	200	220	1	A	18.20
	85D26L	NX110-5	70	56	630	133	260	168	200	220	0	A	18.20
D31	65D31R	N70Z	70	56	600	120	301	172	200	220	1	A	20.50
	65D31L	N70ZL	70	56	600	120	301	172	200	220	0	A	20.50
	105D31R	NX120-7	90	72	750	165	301	172	200	220	1	A	23.10
	105D31L	NX120-7L	90	72	750	165	301	172	200	220	0	A	23.10
CMF	CMF40A	-	40	28	332	52	187	127	199	219	0	B	10.42
	CMF60AL	-	60	48	500	100	242	173	188	188	0	A	14.60
	CMF70L	-	70	56	630	133	275	173	188	188	0	A	17.00
	CMF100R	-	100	80	750	175	324	172	204	224	1	A	24.00
	CMF100L	-	100	80	750	175	324	172	204	224	0	A	24.00
E41	115E41R	N100	100	80	750	175	403	173	209	231	1	A	24.50
	115E41L	N100L	100	80	750	175	403	173	209	231	0	A	24.50
F51	130F51	N120	120	96	850	230	503	182	208	230	4	A	33.50
G51	155G51	N150	150	120	1000	300	503	216	208	230	4	A	41.00
H52	190H52	N200	200	160	1100	430	503	261	217	239	4	A	53.00

FOR EUROPEAN VEHICLES (DIN CMF series)

DIN GROUP	Type No. (DIN)	Capacity 20Hr (A/H)	CCA -18°C CCA (Amps)		MAX. Overall Dimension(mm)				Lay-Out	Terminal	Base Hold down	Weight (KGS)
			DIN	SAE	L	W	H	TH				
L1	54459	44	210	380	208	173	188	188	0	A	B3	12.0
	54464	44	210	380	208	173	188	188	1	A	B3	12.0
L2	55559	55	255	450	242	173	188	188	0	A	B3	14.6
	55565	55	255	450	242	173	188	188	1	A	B3	14.6
	56219	62	280	500	242	173	188	188	0	A	B3	15.5
	56220	62	280	500	242	173	188	188	1	A	B3	15.5
L3	56638	66	300	550	275	173	188	188	0	A	B3	17.0
	57412	74	350	650	275	173	188	188	0	A	B3	18.0
	57413	74	350	650	275	173	188	188	1	A	B3	18.0
L5	58827	88	395	750	354	173	188	188	0	A	B3	22.0
	60038	100	450	800	354	173	188	188	0	A	B3	23.0
L7	67018	170	600	1050	503	216	193	214	3	A	-	42.0